

## Two Stage Pumps

### Solid CAST IRON Piston Pumps

**Factory Direct**

- Flow-Tek™: Concentric Disc Valves deliver maximum air flow and reliability with low replacement costs

**Model# APP3Y0732T**

7.5HP 3 Cylinder 32 CFM



Flywheel Rear View

**Model# APP2I0524T**

5HP 2 Cylinder Inline 24 CFM



**Model# APP3Y0521T**

5HP 3 Cylinder 21 CFM



- Quiet, Low RPM Solid Cast Iron construction for extened life - up to 50,000 hours\*

Model	APP3Y0521T	APP2I0524T	APP3Y0732T
CFM Displacement	21	24	32
CFM @ 100 PSI	18	19	26
Maximum PSI	175	175	175
Pump RPM	820	820	820
Noise DB(A)	75	75	74
Bolt Pattern	9 7/8" x 6 1/2"	7 3/4" x 9"	9 7/8" x 6 1/2"
Belt Type	B	B	B
Belt Number	2	2	2
Outlet	NPT 3/4"	NPT 3/4"	NPT 3/4"
Ship Weight (lbs.)	162	230	170
Dimensions: LxWxH	23" x 13" x 18"	18" x 20" x 21"	23" x 16" x 18"



ASME International